BR 714 025 ClassicLine hand-held eye shower with two spray heads 45°, wall or table mounted

ClassicLine hand-held eye shower with two spray heads 45°, wall or table mounted
- ergonomically shaped handle with integrated, adjusting activation made of plastics, valve not self-closing
- high-performance spray heads for large-scale dispersion of water, 45° angled, with plastic spray plate, largely free of calcification, with rubber sleeves and sealed dust caps
- integrated flow regulation 14 litre / minute for a standard-compliant jet pattern at a specified working range of 2.5 to 5 bar flow pressure
- integrated backflow preventer to protect the drinking water
- stainless steel covered hose, length 1.5 meter, water inlet ½" female, DIN-DVGW tested and certificated
- robust table and wall mounting bracket with positioning of the shower, accessories M28x1,5x80mm made of stainless steel, incl. fastening-parts kit with nut M28x1,5mm and 2 screws M5 for mounting difficult to access, sealing to table surface with O-Ring
- sign for eye shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 100 x 100 mm, viewing distance 10 metre
- mounting height 700 mm (± 200 mm)
- according to BGI/GUV-I 850-0, DIN 1988 and EN 1717
- according to ANSI Z358.1-2014 and EN 15154-2:2006
- DIN-DVGW tested and certificated

Manufacturer: B-SAFETY or equal
Article-No.: BR 714 025

Technical Specifications
Minimum flow pressure: 2.5 bar
Operating pressure: 2.5 to 5 bar
Flow rate: 14 l/min
Water inlet: ½" female

B-SAFETY PROFESSIONAL SAFETY SOLUTIONS

B-SAFETY GmbH - Oststraße 85 - DE-22844 Norderstedt
Fon: +49-(0)40/53 80 92-70 - Fax: +49-(0)40/53 80 92-86
Web: www.b-safety.com - E-Mail: info@b-safety.com