## BR 852 085 ClassicLine eye-/face wash unit with bowl and lid, floor mounted

ClassicLine eye-/face wash unit with bowl and lid, floor mounted
- base plate with 4 mounting holes of stainless steel, chemical resistant green powder coated, dimensions 200 x 200 mm
- stand pipe 1 ¼" of stainless steel, chemical resistant green powder coated, with top and bottom water inlet 1 ¼" female, total height 1025 mm
- housing, lid and bowl made of UV and impact resistant ABS plastics, water outlet 1 ½" male
- integrated protective cover against dust
- actuation by pulling down the lid
- ball valve 3/8" of stainless steel, with lever actuation by lid, DIN-DVGW tested and certificated
- aerators made of brass with a very limited spray pattern, chrome-plated
- with integrated flow regulation valve 3/8" for setting the desired spray height and flow rate, water inlet 3/8" male
- inclusive sign for eye shower according to DIN EN ISO 7010 und ASR A1.3 on the lid, dimensions 170 x 170 mm, viewing distance 17 metre
- height 1025 mm, width 350 mm, depth 355 mm
- mounting height (lower edge) 910 mm (± 200 mm)
- according to BGI/GUV-I 850-0, DIN 1988 and DIN EN 1717
- according to ANSI Z358.1-2014 and DIN EN 15154-2:2006
- DIN-DVGW tested and certificated

Manufacturer: B-SAFETY or equal
Article-No.: BR 852 085

**Technical Specifications**
Minimum flow pressure: 2.5 bar
Operating pressure: 2.5 to 5 bar
Flow rate: 14-20 l/min
Water inlet: 1 ¼" female
Water outlet: 1 ½" male



B-SAFETY® PROFESSIONAL SAFETY SOLUTIONS

B-SAFETY GmbH - Oststraße 85 - DE-22844 Norderstedt
Fon: +49-(0)40/53 80 92-70 - Fax: +49-(0)40/53 80 92-86
Web: www.b-safety.com - E-Mail: info@b-safety.com