

[www.b-safety.com](http://www.b-safety.com)

**BR 834 095 PremiumLine body safety shower with hand-held eye shower with two spray heads 45°, floor mounted**

PremiumLine body safety shower with hand-held eye shower with two spray heads 45°, floor mounted

- including top and bottom water inlet 1 ¼" female for installation in circulation lines, plug 1 ¼" of stainless steel
- base plate with 4 mounting holes of stainless steel, polished, diameter 200 mm
- stand pipe 1 ¼" of stainless steel three-part, polished, with top and bottom water inlet 1 ¼" female, total height 2330 mm
- connection piece of stainless steel, for easy installation and alignment of the shower
- ball valve ¾" of stainless steel, with quick connect system and pull rod actuation, DIN-DVGW tested and certificated
- pull rod with ring handle of stainless steel, polished, length 700 mm
- wall shower arm ¾" of stainless steel, polished, projection 630 mm
- integrated automatic flow regulation 50 l/min. for a spray pattern acc. to the norms at a specified operating range of 1.5 to 3 bar dynamic water pressure
- high-performance shower head of stainless steel, polished, with improved spray pattern, corrosion resistant, largely free of calcification-and maintenance, very robust, self-draining
- sign for body safety shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 150 x 150 mm, viewing distance 15 metre
- inclusive ClassicLine hand-held eye shower with two spray heads 45°, for mounting on standpipe, position and orientation freely selectable
- ergonomically shaped handle with integrated, adjusting activation made of plastics, valve not self-closing
- high-performance spray heads for large-scale dispersion of water, 45° angled, with plastic spray plate, largely free of calcification, with rubber sleeves and sealed dust caps with folding mechanism
- integrated flow regulation 14 litre / minute for a standard-compliant jet pattern at a specified working range of 2 to 5 bar flow pressure
- integrated backflow preventer to protect the drinking water
- stainless steel covered hose, length 1.5 meter, water inlet ½" female, DIN-DVGW tested and certificated
- sturdy wall bracket with positioning of the shower, including mounting kit for mounting on the standpipe
- sign for eye shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 100 x 100 mm, viewing distance 10 metre
- according to BGI/GUV-I 850-0, DIN 1988 and EN 1717
- according to ANSI Z358.1-2014, EN 15154-1:2006, EN 15154-2:2006 and EN 15154-5:2019
- DIN-DVGW tested and certificated

Manufacturer: B-SAFETY or equal  
 Article-No.: BR 834 095

**Technical Specifications**

Minimum flow pressure: 1.5 bar  
 Operating pressure: 1.5 to 3 bar  
 Flow rate body shower: 50 l/min  
 Flow rate eye shower: 14 l/min  
 Water inlet: 1 ¼" female

**Product overview**

**BR 834 095:** flow rate 50 l/min (hazard class I according to EN 15154-5:2019)  
**BR 834 095 / 75L:** flow rate 75 l/min / 20 GPM (hazard class II according to EN 15154-5:2019)  
**BR 834 095 / 110L:** flow rate 110 l/min (hazard class III according to EN 15154-5:2019)