

**BR 863 095**

**PremiumLine safety shower combination, with hand-held eye shower, wall mounted, exposed pipework**

- PremiumLine safety shower combination, with hand-held eye shower, wall mounted, exposed pipework
- including top and bottom water inlet 3/4" female for installation in circulation lines, plug 3/4" of stainless steel
  - wall flange with 4 mounting holes of stainless steel, polished, water inlet 3/4" female
  - connection piece 3/4" of stainless steel, for easy installation and alignment of the shower
  - ball valve 3/4" of stainless steel, with quick connect system and pull rod actuation, DIN-DVGW tested and certificated
  - pull rod with ring handle of stainless steel, polished, length 700 mm
  - wall shower arm 3/4" of stainless steel, polished, projection 625 mm
  - integrated automatic flow regulation 50 l/min. for a spray pattern acc. to the norms at a specified operating range of 1.5 to 3 bar dynamic water pressure
  - high-performance shower head of stainless steel, polished, with improved spray pattern, corrosion resistant, largely scale and maintenance-free, very robust, self-draining
  - sign for body safety shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 150 x 150 mm, viewing distance 15 metre
  - two connection pipes 3/4" of stainless steel, polished, total length 1500 mm
  - wall flange with 4 mounting holes of stainless steel, polished, water inlet 3/4" female
  - inclusive ClassicLine hand-held eye shower with one spray head 45°, wall mounted
  - ergonomically shaped handle with integrated, adjusting activation made of plastics, valve not self-closing
  - high-performance spray head for large-scale dispersion of water, 45° angled, with plastic spray plate, largely scale-free, with rubber sleeves and sealed dust caps
  - integrated flow regulation 7 litre / minute for a standard-compliant jet pattern at a specified working range of 1.5 to 5 bar flow pressure
  - integrated backflow preventer to protect the drinking water
  - stainless steel covered hose, length 1.5 meter, water inlet 1/2" female, DIN-DVGW tested and certificated
  - robust table and wall mounting bracket with positioning of the shower, accessories M28x1,5x80mm, incl. fastening-parts kit with nut M28x1,5mm and 2 screws M5 for mounting difficult to access, sealing to table surface with O-Ring
  - sign for eye shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 100 x 100 mm, viewing distance 10 metre
  - mounting height 810 mm (± 100 mm)
  - according to BGI/GUV-I 850-0, DIN 1988 and EN 1717
  - according to ANSI Z358.1-2014, EN 15154-1:2006, EN 15154-2:2006 and EN 15154-5:2019
  - DIN-DVGW tested and certificated
- Manufacturer: B-SAFETY or equal  
 Article-No.: BR 863 095

**Technical Specifications**

- Minimum flow pressure: 1.5 bar
- Operating pressure: 1.5 to 3 bar
- Flow rate body shower: 50 l/min
- Flow rate eye shower: 7 l/min
- Water inlet: 3/4" female

**Product overview**

- BR 863 095:** flow rate 50 l/min (hazard class I according to EN 15154-5:2019)
- BR 863 095 / 75L:** flow rate 75 l/min / 20 GPM (hazard class II according to EN 15154-5:2019)
- BR 863 095 / 110L:** flow rate 110 l/min (hazard class III according to EN 15154-5:2019)