

www.b-safety.com

BR 867 095

PremiumLine safety shower combination, with safety eye shower with stainless steel bowl, wall mounted, exposed pipework

- PremiumLine safety shower combination, with safety eye shower with stainless steel bowl, wall mounted, exposed pipework
- including top and bottom water inlet 3/4" female for installation in circulation lines, plug 3/4" of stainless steel
 - wall flange with 4 mounting holes of stainless steel, polished, water inlet 3/4" female
 - connection piece 3/4" of stainless steel, for easy installation and alignment of the shower
 - ball valve 3/4" of stainless steel, with quick connect system and pull rod actuation, DIN-DVGW tested and certificated
 - pull rod with ring handle of stainless steel, polished, length 700 mm
 - wall shower arm 3/4" of stainless steel, polished, projection 625 mm
 - integrated automatic flow regulation 50 l/min. for a spray pattern acc. to the norms at a specified operating range of 1.5 to 3 bar dynamic water pressure
 - high-performance shower head of stainless steel, polished, with improved spray pattern, corrosion resistant, largely scale and maintenance-free, very robust, self-draining
 - sign for body safety shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 150 x 150 mm, viewing distance 15 metre
 - two connection pipes 3/4" of stainless steel, polished, total length 1500 mm
 - wall flange with 4 mounting holes of stainless steel, polished, water inlet 3/4" female
 - integrated PremiumLine safety eye shower with stainless steel bowl
 - connection pipe of stainless steel for easy installation and alignment of the shower, polished
 - ball valve 1/2" of stainless steel, with PUSH-lever actuation, DIN-DVGW tested and certificated
 - big push plate made of stainless steel, polished, length 240 mm, with large signal "PUSH", luminescent according to DIN 67510
 - integrated flow regulation 14 litre / minute for a standard-compliant jet pattern at a specified working range of 2.5 to 5 bar flow pressure
 - high-performance spray heads made of stainless steel for large-scale dispersion of water, with plastic spray plate, largely scale-free, with rubber sleeves and sealed dust caps
 - bowl made of stainless steel, diameter 275 mm, polished, water outlet 1 1/4" male
 - sign for eye shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 100 x 100 mm, viewing distance 10 metre
 - mounting height 810 mm (± 100 mm)
 - according to BGI/GUV-I 850-0, DIN 1988 and EN 1717
 - according to ANSI Z358.1-2014, EN 15154-1:2006, EN 15154-2:2006 and EN 15154-5:2019
 - DIN-DVGW tested and certificated
- Manufacturer: B-SAFETY or equal
 Article-No.: BR 867 095

Technical Specifications

- Minimum flow pressure: 1.5 bar
- Operating pressure: 1.5 to 3 bar
- Flow rate body shower: 50 l/min
- Flow rate eye shower: 14 l/min
- Water inlet: 3/4" female

Product overview

- BR 867 095:** flow rate 50 l/min (hazard class I according to EN 15154-5:2019)
- BR 867 095 / 75L:** flow rate 75 l/min / 20 GPM (hazard class II according to EN 15154-5:2019)
- BR 867 095 / 110L:** flow rate 110 l/min (hazard class III according to EN 15154-5:2019)