

www.b-safety.com

BR 085 095 / V PremiumLine variable body safety shower, ceiling mounted, exposed pipework

PremiumLine variable body safety shower, ceiling mounted, exposed pipework

- ceiling flange with 4 mounting holes of stainless steel, polished, water inlet $\frac{3}{4}$ " female
- ball valve $\frac{3}{4}$ " of stainless steel, with pull rod actuation, DIN-DVGW tested and certificated
- pull rod with ring handle of stainless steel, polished, length variable (min. 855 mm - max. 1660 mm)
- ceiling shower arm $\frac{3}{4}$ " of stainless steel, polished, headroom variable according to specification (min. 420 mm - max. 1225 mm)
- integrated automatic flow regulation 50 l/min. for a spray pattern acc. to the norms at a specified operating range of 1.5 to 3 bar dynamic water pressure
- high-performance shower head of stainless steel, polished, with improved spray pattern, corrosion resistant, largely calcification- and maintenance-free, very robust, self-draining
- sign for body safety shower according to EN ISO 7010 und ASR A1.3, self-adhesive PVC-film, 150 x 150 mm, viewing distance 15 metre
- mounting height according to the standards listed below: lower edge of high-performance shower head 2200 mm (± 100 mm) height above floor level
- according to BGI/GUV-I 850-0, DIN 1988 and EN 1717
- according to ANSI Z358.1-2014, EN 15154-1:2006 and EN 15154-5:2019
- DIN-DVGW tested and certificated

Manufacturer: B-SAFETY or equal

Article-No.: BR 085 095 / V

Technical Specifications

Minimum flow pressure: 1.5 bar

Operating pressure: 1.5 to 3 bar

Flow rate: 50 l/min

Water inlet: $\frac{3}{4}$ " female

Product overview

BR 085 095 / V: flow rate 50 l/min (hazard class I according to EN 15154-5:2019)

BR 085 095 / V75L: flow rate 75 l/min / 20 GPM (hazard class II according to EN 15154-5:2019)

BR 085 095 / V110L: flow rate 110 l/min (hazard class III according to EN 15154-5:2019)